

# HIGHLIGHT HL-ML-ALM



The design of solar street light / courtyard light absorbs energy from the universe, and combines it with high efficiency solar panel, LEDs, and Lithium battery. It adopts advantage technics such as micro-controller, human infrared sensor and so on and combines with integrated design to achieve multiple features such as low power consumption but high brightness, long lifespan and maintenance free, meanwhile with waterproof function and great thermal dissipation. The intelligent control can be reprogrammed from the ground with an infrared before and after install. It is one of our great innovation patented products.



## Key features:

- Low installation and maintenance costs.
- IP66 Rating.
- High performance 1W LEDs with 200lm/w.
- Light dimming engine.
- Led's operating life time over 100,000 hours at maximum output.
- PTC Auto-heating system.
- Adjustable LED .
- Adjustable mounting bracket.
- LED strings shunt protection.
- Ideal for solar or energy saving electrical applications.
- Aluminum housing for efficient heat dissipation
- Approved IDA

## Uses and Applications Guide

Mid-size roads	●
Streets lighting	●
Parking lots	●
Boardwalks	●
Farms	●
Public parks	●
Private gardens	●
Access roads	●
Walking paths	●

## Technical specifications

Solar Module Parameters	Type	Monocrystalline Silicon
	Power	Up to 135W
Solar Charge Controller Parameters	Type	MPPT
Battery Parameters	Type	Li-ion
	Capacity	Up to 60AH
LED Light Parameters	Light Source Power	Up to 100W
	Lamp Rated Total Luminous Flux	Up to 20,000lm
	Luminous Efficacy	200lm/w
	CCT (Correlated Color Temperature)	3,000K-6,500K
	Color Rendering Index (CRI)	≥ 82
Operation profiles	6hrs- 100%; 25% to dawn	
	4hrs- 100%; 25% to dawn	
	1hr-100%; 3hrs-50%; 25% to dawn	
	1hr-100% ; 2hrs-80%; 3-4hrs-60; 5hrs-25% 5H 25% to dawn	
	5. 100% dusk to dawn	
	6. Customized	
* Operation profile above are active depending to the solar radiation in the installation location, please consult with one of Solarpath representative.		
Lighting Material	Die-casting Aluminum	
Product size	light body	Depend On LED power
	solar panel	Depend On Solar Panel wattage
Net weight	light body	Depend On LED power
	solar panel	Depend On Solar Panel Wattage

## Ordering Guide: EXAMPLE: HL-ML-ALM-25W-10W-2-30K -10AH-BLK-00-PTC-R

Model	Solar Panel	LED Power	Distribution type	LED Color Temp	Battery Options	Body Color	Options
HL-ML-ALM	25W	10W	2- Type II	30K	10AH	BLK- Black	00- No motion sensor 01-Motion sensor PTC- Warmer R- Round pole mounting S- Square pole mounting WM- Wall mounting
	45W	15W		3- Type III	40K		
	60W	20W	50K		18AH		
	75W	25W	65K		20AH		
	105W	30W	23AH				
	135W	35W	25AH				
	40W	30AH					
	45W	35AH					
	50W	40AH					
	60W	45AH					
	75W	50AH					
	90W	60AH					
	100W						



\*Up on request.

Legal Clarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade names, trademarks, trade symbols, service marks, logos, icons and trade dress of SolarPath Inc or in connection to SolarPath Inc or any of its selling products, contained herein is in the exclusive ownership of SolarPath Inc and may not be alternated and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc. Furthermore, redistribution or any kind of commercial use or alternation or any kind of use other then downloading presented information in some or all contents of downloadable documents, and/or downloadable contents, is strictly prohibited without express written prior permission. All information set out herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not

manage.