

2SPBL13 Architectural Solar LED Light



The 2SPBL13 solar bollard light is an architectural independent lighting solution ideally for various applications such as parks, pathways, bike lanes, remote areas, golf courses, beach resorts, marinas, residential areas and landscape lighting projects.

The architectural patented design in combination with a robust high LED lighting output in a high-grade construction makes it your ideal choice for all your self-contained lighting projects.



2SPBL13 works completely without wiring and gets its power from the sun, using a special energy storage system, which requires no replacement of batteries for several years.

Energy storage and usage is controlled by a unique built-in self-decise software algorithm. Cloudy days or shaded areas, the intelligent energy saving 2SBL13 always provides perfect lighting conditions.

Key Features

- Maintenance free.
- Minimal ongoing costs with no electricity bills
- IP65 Rating.
- Battery level LED display.
- Ease of installation
- IK10 resistance- Optional
- 2 years warranty.

Uses and applications guide

Marinas	●
Gardens	●
Landscaping	●
Walking paths	●
Bike paths	●

Technical Specifications

Solar Power	8W
Battery Capacity	7.4V/10AH
Battery Type	Li-ion Battery
Power of Lamp	3W (up to 400lm)
Distribution type	Type III, type V
Pole Height (Light Included)	Up to 35"
Rainy/Cloudy Days	Depends on solar radiation
Operation Mode	1. Dusk to dawn. 2. Dimming option.
Lighting Technology	NICHIA/ OSRAM LED
Life span	50.000 Hours
CCT	3,000K / 5,000K / 6,000K (other colors available)

Solar Module	Impact Monocrystalline solar panel
Working temperature	-40°F - 140°F
IP Rating	IP65
Body Material	Anodized aluminum alloy

Ordering guide

Example: 2SPBL13- 30K - 3 - BLK - 24"-SC-IK-DS

LED Color	Distribution type	Finish	Height	Install option	Option
2SPBL13	30K***	3 - Type III	BLK - Black	18"	SC-Screws
	50K	5 - Type V	*Other colors upon request	24"	AB-Anchor bolts
	60K			35"	IK-IK10
	*Other colors available.				DS-3,000K or lower must be selected to meet IDA Dark Sky requirements

*** 3,000K or lower must be selected to meet IDA Dark Sky requirements



*Up on request

Distribution Type III



Distribution Type V



Legal Clarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade names, trademarks, trade symbols, service marks, logos, icons and trade dress of SolarPath Inc or in connection to SolarPath Inc or any of its selling products, contained herein is in the exclusive ownership of SolarPath Inc and may not be alternated and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc. Furthermore, redistribution or any kind of commercial use or alternation or any kind of use other than downloading presented information in some or all contents of downloadable documents, and/or downloadable contents, is strictly prohibited without express written prior permission. All information set out herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not manage.