2SPBL18 Architectural Solar LED Light





The 2SPBL18 solar bollard light is an architectural independent lighting solution ideally for various applications such as parks, pathways, bike lanes, remote areas, golf courses, beach resorts, marinas, residential areas and landscape lighting projects.

The architectural patented design in combination with a robust high LED lighting output in a high-grade construction makes it your ideal choice for all your self-contained lighting projects.

2SPBL18 works completely without wiring and gets its power from the sun, using a special energy storage system, which requires no replacement of batteries for several years.

Energy storage and usage is controlled by a unique built-in self-decisive software algorithm. Cloudy days or shaded areas, the intelligent energy saving 2SPBL18 always provides perfect lighting conditions.

Key Features

- Maintenance free.
- Minimal ongoing costs with no electricity bills
- IP65 Rating.
- IK10 resistance
- Quick and easy installation
- Vandal resistant

Uses and applications guide


Marinas	
Gardens	
Landscaping	
Walking paths	
Bike paths	

Technical Specifications

Solar Power 6.2W Battery Capacity 12AH Battery Type LifePO4 Power of Lamp 1.5w (280lm) Distribution type 120 degree Lighting Technology NICHIA/OSRAM LED Pole Height 35.43" Rainy/Cloudy Days Depends on solar radiation Operation Mode Dimming option	
Battery Type LifePO4 Power of Lamp 1.5w (280lm) Distribution type 120 degree Lighting Technology NICHIA/OSRAM LED Pole Height 35.43" Rainy/Cloudy Days Depends on solar radiation Operation Mode Dimming option	
Power of Lamp Distribution type Lighting Technology Pole Height Rainy/Cloudy Days Operation Mode Dimming option 1.5w (280lm) D1.5w (280lm) D1	
Distribution type 120 degree Lighting Technology NICHIA/OSRAM LED Pole Height 35.43" Rainy/Cloudy Days Depends on solar radiation Operation Mode Dimming option	
Lighting Technology Pole Height Rainy/Cloudy Days Operation Mode NICHIA/OSRAM LED 35.43" Depends on solar radiation Dimming option	
Pole Height 35.43" Rainy/Cloudy Days Depends on solar radiation Operation Mode Dimming option	
Rainy/Cloudy Days Depends on solar radiation Operation Mode Dimming option	
Operation Mode Dimming option	
, , ,	
CCT 3,000K-6,000K	
Solar Module Impact Monocrystalline solar panel	
Working temperature 5°F - 158°F	
IP Rating IP65	
Body Material Aluminum die casting +PC + tempered Glass	


Ordering guide

Example: 2SPBL18-30K - BLK - 35.43"-IK-BT-DS



^{*** 3,000}K or lower must be selected to meet IDA Dark Sky requirements









Legal Clarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade names, trade arms, trade symbols, service marks, logos, icons and trade dress of SolarPath Inc or in connection to SolarPath Inc or any of its selling products, contained herein is in the exclusive ownership of SolarPath Inc and may not be alternated and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc. Furthermore, redistribution or any kind of commercial use or alternation or any kind of use other then downloading presented information in some or all contents of downloadable documents, and/or downloadable contents, is strictly prohibited without express written prior permission. All information set out herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not manage.